

Cee-Bee[®] A-458

Cee-Bee[®] A-458 is specifically designed for removing polysulfide basecoat paint systems. Also used for stripping polysulfide sealants and similar sealing compounds.

Conforms To

- Military
 - MIL-R-81294C
 - Type III, Class 2
 - T.O.1-1-8
 - Section II

Benefits

- Provides excellent removal of polyurethane and other paint systems with polysulfide basecoats.
- Very effectively removes polysulfide sealants and similar sealants as well as natural rubber base sealants and coatings.
- Thixotropic. Clings to vertical, inclined and overhead surfaces.
- Contains evaporation retardant to minimize solvent loss.
- Free rinsing.
- Safe on aircraft structural metals, including high strength steel, mild steel, stainless steel, cadmium plated steel, aluminum, and magnesium.
- Contains no phenol, heavy metals or mercaptans.

Properties

- Thick, light colored liquid

Notes Prior to Handling

Before using your Cee-Bee[®] products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee[®] representative before proceeding.

Use Procedure

Coating Removal

1. The surface must be thoroughly clean, free from water and preferably at a temperature below 100°F (38°C). 60 to 90°F (16-32°C) is desirable.
2. Flow on or apply Cee-Bee[®] A-458 by brush or non-atomizing spray. Allow stripper to dwell until coating is penetrated and swells. Apply additional Cee-Bee[®] A-458 if required to keep the surface wet with stripper.
3. When the coating is completely lifted from the substrate, thoroughly agitate with a stiff bristle brush. Apply more stripper to areas still adhering to the surface.
4. When stripping action is complete, thoroughly rinse surface with a high-pressure water spray.

Sealant Removal

1. The surface must be thoroughly clean, free from water and at a temperature below 100°F (38°C) is desirable.
2. Apply Cee-Bee[®] A-458 with a brush. Allow stripper to dwell until sealant is penetrated and dissolved. Apply additional stripper if required to keep surface wet.
3. When sealant is completely lifted from substrate, remove with scraper which will not scratch surface. Reapply stripper to any spots of sealant which are not readily removed with a scraper.
4. When removal is complete, flush surface with a spray rinse of water or wipe clean with cloths wet with water.

Safety, Handling, and Precautions

- Contains methylene chloride.
- Do not use in confined spaces. Adequate ventilation must be provided. Avoid breathing vapors.
- Avoid all eye and skin contact. Use face shield, apron, gloves and boots.
- In case of accidental contact with eyes or skin, flood with water immediately. Seek medical attention if irritation persists.
- Open containers slowly to avoid spewing of contents.
- Do not contaminate bath with water. Water contamination will adversely affect stripping performance.

Contact Us

United States

McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: Aviation@McGean.com

United Kingdom

McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: Aviation@McGean-Rohco.co.uk

Singapore

McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: Info@ceebee.com.sg

China

Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: Info@ceebee.com.cn

Cee-Bee[®] A-458 is a specifically designed for removing polysulfide basecoat paint systems. Also used for stripping polysulfide sealants and similar sealing compounds.

CAUTION: BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 06/2021 (Rev. A2)