

## Cee-Bee<sup>®</sup> A-952

Cee-Bee<sup>®</sup> A-952 is a solvent type remover for corrosion inhibiting compounds.

### Conforms To

- Airbus
  - Application Code: 08ABC1
  - CML 11-001
  - Product Code: 860100
- AMS
  - AMS 1526
- Boeing
  - D6-17487 (Rev. T)
  - D6-7127 (Rev. P)
- Douglas
  - DPM 6561
- Goodrich Corp.
  - Wheel and Brakes
- Honeywell
  - SPM 32-49-01
- Rolls Royce
  - OMat 1/267D

### Benefits

- Slow evaporation rate.
- Excellent solvency for removing corrosion inhibitors and temporary coatings, as well as for grease and greasy soils.
- Removes double sided tapes and chewing gum.
- Safe for use on most painted surfaces when used as directed.
- Low vapour toxicity. Safer than methyl ethyl ketone (MEK), toluene or xylene. Safer than halogenated solvents.
- This product will not damage the earth's ozone layer.
- Contains no phenolics, cyanides, nitrates, heavy metal salts or hazardous solvents. This product does not contain methylene chloride or any other halogenated solvent.

### Properties

- Water thin liquid
- Hydrocarbon odor

### Notes Prior to Handling

Before using your Cee-Bee<sup>®</sup> products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee<sup>®</sup> representative before proceeding.

## Use Procedure

---

### General Cleaning with Water Rinse

1. Apply remover using non-atomizing spray, mops or brushes.
2. Allow remover to dwell at least 5 minutes or until the coating is penetrated, then agitate the surface with a brush or mop.
3. Rinse thoroughly with high pressure water.

### General Cleaning Without Water Rinse

1. Wipe surface clean, using clean cloths or nylon fleece scrubbing pads wet with cleaner. Turn frequently to prevent redeposition of soil or residues on cleaned surface.
2. Wipe with clean, dry cloths. If surface is to be air dried, all residual soil must be wiped.

### For removal of CICs from Cargo Areas or other large areas:

1. Apply cleaner with non-atomizing spray (A 5:1 Ratio Stainless Steel 5:1 drum pump is ideal).
2. Allow cleaner to dwell 5-15 minutes or until soils are penetrated. Thicker CIC coatings may require agitation with a brush to improve penetration.
3. Rinse thoroughly with a high-pressure flow of warm water.

## Safety, Handling, and Precautions

---

- Contains concentrated solvents.
- Avoid eye and skin contact. Use rubber gloves and face shield or goggles. Some form of eye protection is always absolutely essential.
- Use with adequate ventilation.
- Do not use in confined areas. If ventilation is inadequate, use a NIOSH - certified respirator which will protect against organic vapor and dust/mist.
- Do not take internally.
- For contact with eyes or skin, flood with water. If eye irritation persists, seek medical attention.
- For inhalation, remove to fresh air.
- Store containers in a cool dry area. Open containers slowly to prevent any spewing of contents. Keep containers tightly sealed. Before using on plastic electrical insulation or a painted surface that might be damaged, check effect on samples.

## Contact Us

---

### United States

#### McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: [Aviation@McGean.com](mailto:Aviation@McGean.com)

### United Kingdom

#### McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: [Aviation@McGean-Rohco.co.uk](mailto:Aviation@McGean-Rohco.co.uk)

---

### Singapore

#### McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: [Info@ceebee.com.sg](mailto:Info@ceebee.com.sg)

### China

#### Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: [Info@ceebee.com.cn](mailto:Info@ceebee.com.cn)

**Cee-Bee<sup>®</sup> A-952** is a solvent type remover for corrosion inhibiting compounds.

**CAUTION:** BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 01/2023 (Rev. A3)