

Cee-Bee[®] C-50

Cee-Bee[®] C-50 is a rapidly-evaporating safety solvent to replace flammable cleaning solvents, such as methyl ethyl ketone (MEK) and toluene.

Conforms To

- Douglas
 - DPM 5069
- Grumman Aerospace
 - GS1151W1
- Lockheed
 - AMMC

Benefits

- Excellent solvency for greasy and oily soils and most organic soils.
- Excellent wipe solvent for paint residue removal.
- Evaporates completely leaving no solvent residue.
- Safe for use on common structural metals, including steel, high strength steel, aluminum, magnesium and copper alloys.
- Non-photochemically reactive - does not contribute to air pollution.
- Low vapor toxicity.

Properties

- Water thin, colorless to slightly amber liquid
- Blend of chlorinated and oxygenated solvents
- Mild odor

Notes Prior to Handling

Before using your Cee-Bee[®] products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee[®] representative before proceeding.

Use Procedure

Remove Greases and Shop Soils

1. Wipe off soils with clean cloths wet with Cee-Bee[®] C-50.
2. Turn cloths frequently to prevent re-deposition of soils on cleaned surface.
3. Allow surface to air dry or wipe dry with clean cloths.

Remove Residues After Paint Stripping

1. Use clean cloth or nylon fleece scrubbing pad wet with Cee-Bee[®] C-50 to wipe off paint and primer residues.
2. Wipe surface dry with clean, dry cloths if desired.

Reactivate Primed Surfaces Prior To Applying Topcoat

1. If primed surface is allowed to dwell more than 24 hours before top coating, reactivate and clean surface by wiping with clean cloths wet with Cee-Bee[®] C-50. If desired, wipe dry with clean, dry cloths.
2. Paint immediately.

Remove Chewing Gum from Carpets and Upholstery

1. Apply liberal quantity of Cee-Bee[®] C-50 to absorbent cloth and dab chewing gum and surrounding area.
2. Leave for 2 to 3 minutes.
3. Remove brittle gum with a scraper and area again with Cee-Bee[®] C-50 to remove any residue.

Safety, Handling, and Precautions

- **DANGER!** CONTAINS CHLORINATED HYDROCARBONS WHICH CAN CAUSE EYE BURNS.
- Avoid contact with skin, eyes and clothing. Open container slowly to avoid spewing of contents.
- Do not use in confined spaces. Adequate ventilation must be provided.
- Avoid prolonged exposure to vapor.
- In case of accidental contact with liquid, wash thoroughly with soap and water; flush eyes with water for at least 15 minutes and call a doctor.
- Do not take internally.
- Cee-Bee[®] C-50 will attack acrylic, styrene and some other plastics. Avoid contact to prevent damage. When Cee-Bee[®] C-50 is to be used on plastic of unknown composition, apply Cee-Bee[®] C-50 to a test specimen of the plastic and examine for possible damage prior to use.
- To prevent selective evaporation of the components of Cee-Bee[®] C-50 during storage, keep container tightly sealed.
- Avoid prolonged storage temperatures above 100°F (38°C).

Contact Us

United States

McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: Aviation@McGean.com

United Kingdom

McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: Aviation@McGean-Rohco.co.uk

Singapore

McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: Info@ceebee.com.sg

China

Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: Info@ceebee.com.cn

Cee-Bee[®] C-50 is a rapidly-evaporating safety solvent to replace flammable cleaning solvents, such as methyl ethyl ketone (MEK) and toluene.

CAUTION: BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 06/2021 (Rev. A2)