

## Cee-Bee<sup>®</sup> E-1058

Cee-Bee<sup>®</sup> E-1058 is a non-toxic, thixotropic stripper specifically designed for removing polysulfide basecoat paint systems, polysulfide sealants and similar adhesives.

### Conforms To

- Grumman Aerospace
  - GS115UT1
- Military
  - T.O. 1-1-8, Section II

### Benefits

- Contains no halogenated solvents, phenol, heavy metals or mercaptans.
- Provides excellent removal of polyurethane and other paint systems with polysulfide basecoats.
- Effectively removes polysulfide sealants and similar sealants, as well as natural rubber base sealants and coatings.
- Thixotropic. Clings to vertical, inclined and overhead surfaces.
- Free rinsing.
- Safe on all aircraft structural metals, including high strength steel.

### Properties

- Thick, clear, colorless liquid
- Mild odor

### Notes Prior to Handling

Before using your Cee-Bee<sup>®</sup> products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee<sup>®</sup> representative before proceeding.

## Use Procedure

---

### Paint Removal

1. The surface to be stripped should be thoroughly clean and free from water.
2. Spray on a light coat of Cee-Bee® E-1058 using a high-pressure 10:1 (or larger) air-activated pump equipped with a 1/2" ID high-pressure hose and spray wand with fan type spray nozzle. It is important to use the correct type of spray nozzle for this type of application. For questions regarding a suitable nozzle, please contact your Cee-Bee® Representative.
3. It is important to use the correct type of spray nozzle for this application. A suitable nozzle is manufactured by Spraying Systems Co. Wheaton, IL. (708-665-5000), nozzle number 6508, fan-type.
4. Keep the surface wet with Cee-Bee® E-1058 until the paint buckles.
5. When the paint is lifted (one hour to overnight for tough coatings), brush the surface thoroughly to remove the loosened paint.
6. Reapply Cee-Bee® E-1058 as required to loosen any remaining paint.
7. When all of the paint has been lifted, use a brush or squeegee to remove the loosened paint and residual stripper.
8. Thoroughly rinse the surface with high pressure water.

### Sealant Removal

1. The surface must be thoroughly clean and free from water.
2. Apply Cee-Bee® E-1058 with a brush and allow to dwell until the sealant is penetrated and dissolved. Apply additional stripper if required to keep the surface wet.
3. When the sealant is dissolved, remove with a suitable scraper that will not scratch the surface. Reapply Cee-Bee® E-1058 to any spots of sealant not readily removed with the scraper.
4. When removal is complete, thoroughly rinse the surface with a water spray or wipe clean with cloths wet with water.

## Safety, Handling, and Precautions

- May irritate eyes and skin - avoid contact.
- Use face shield, gloves and other protective clothing sufficient to prevent contact. Some form of eye protection is always absolutely essential.
- Concentrated vapors may cause irritation. Use in well ventilated area.
- Proper attention should always be paid to environmental considerations.
- In case of accidental contact with eyes or skin, flush area with water immediately. If irritation persists, seek medical attention.
- **DO NOT CONTAMINATE WITH WATER.** Water contamination will adversely affect stripping performance.

## Contact Us

---

### United States

#### McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: [Aviation@McGean.com](mailto:Aviation@McGean.com)

### United Kingdom

#### McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: [Aviation@McGean-Rohco.co.uk](mailto:Aviation@McGean-Rohco.co.uk)

---

### Singapore

#### McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: [Info@ceebee.com.sg](mailto:Info@ceebee.com.sg)

### China

#### Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: [Info@ceebee.com.cn](mailto:Info@ceebee.com.cn)

**Cee-Bee<sup>®</sup> E-1058** is a non-toxic, thixotropic stripper specifically designed for removing polysulfide basecoat paint systems, polysulfide sealants and similar adhesives.

**CAUTION:** BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 06/2021 (Rev. A2)