

Cee-Bee[®] E-2060

Cee-Bee[®] E-2060 is a non-toxic, hydrogen peroxide-activated paint stripper designed for removing polyurethane, epoxy and other paint systems.

Conforms To

- AMS
 - AMS 1376B
- BAE Systems
 - MPE.DW.0001.08
- Boeing
 - D6-17487 (Rev. M) – except magnesium immersion corrosion
- Douglas
 - CSD-1
 - DPM 5549
- United Airlines
 - CSM 5.01
- Vought
 - 208-9-151

Benefits

- Contains no halogenated solvents, phenol, heavy metals or other toxic materials.
- Provides excellent removal of polyurethane, epoxy and other paint systems.
- Thixotropic - Clings to vertical, inclined and overhead surfaces.
- Slow drying for maximum reaction time.
- Safe on all aircraft structural metals (except magnesium) including high strength steel.

Properties

- Viscous liquid
- Mild odor

Notes Prior to Handling

Before using your Cee-Bee[®] products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee[®] representative before proceeding.

Use Procedure

Application Procedures

1. Optimum performance is attained at temperatures between 75 - 87°F (24 - 30°C).
2. The surface to be stripped should be clean and completely dry.
3. Spray an even, medium coat of Cee-Bee® E-2060, starting from the bottom of the aircraft and working upward.
4. Keep the surface wet with stripper until the paint buckles.
5. When the paint is lifted, agitate the surface to remove the loosened paint.
6. Reapply stripper as required.
7. When all of the paint has been lifted, use a brush or squeegee to remove the loosened paint and residual stripper.
8. For best results, apply a mild alkaline cleaning solution (Super Bee™ 210) to effectively remove paint and stripper residue.
9. Thoroughly rinse the surface with water.

Equipment Recommendations

- Use a high-pressure (5:1 or 10:1) air-activated pump equipped with a 0.5 in (1.3 cm) inside diameter high-pressure hose and spray wand with a fan-type spray nozzle.
- Apply the stripper using a pump inlet pressure between 80 to 110 psi.
- For questions regarding suitable pumps or spray nozzles required for this application, please contact your Cee-Bee® representative.

Safety, Handling, and Precautions

- Skin or eye contact can cause irritation. Chemical goggles, face shield, chemical-resistant gloves and protective clothing sufficient to avoid contact are recommended.
- In case of accidental contact, flush area thoroughly with water. If irritation persists, seek medical attention.
- Do not take internally.
- Use in well-ventilated areas.
- **Do not store used stripper and removed coatings in closed container as an exothermic (severe heat) reaction may occur.**
- **Spent drums from Cee-Bee® E-2060 should be thoroughly rinsed before disposal.**
- **If used stripper is placed back into the original Cee-Bee® E-2060 drums, these drums MUST first be rinsed thoroughly and only closed with a vented cap.**

Contact Us

United States

McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: Aviation@McGean.com

United Kingdom

McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: Aviation@McGean-Rohco.co.uk

Singapore

McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: Info@ceebee.com.sg

China

Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: Info@ceebee.com.cn

Cee-Bee® E-2060 is a non-toxic, hydrogen peroxide-activated paint stripper designed for removing polyurethane, epoxy and other paint systems.

CAUTION: BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 06/2021 (Rev. A2)