

## Cee-Bee® J-91

Cee-Bee® J-91 is a diphase, highly active, cold paint, dry film lubricant, and resistant coatings remover.

### Conforms To

- ARP
  - ARP 1755A
- ASTM
  - ASTM-F-945
- Rolls Royce
  - OMat 1/56B

### Benefits

- Extremely active on tough cured epoxy paint systems.
- Contains an oil seal to control moisture pickup.
- Safe on stainless steel, aluminum and titanium when used as directed.
- Does not contain organic solvents or phenolics.

### Properties

- Brown diphase liquid

### Notes Prior to Handling

Before using your Cee-Bee® products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee® representative before proceeding.

## Use Procedure

---

- Use rigid high-density polyethylene or polypropylene tanks, or steel tanks lined with these materials for containing Cee-Bee® J-91.

### Paint Removal

1. Carefully charge tank with Cee-Bee® J-91 as received. Use at ambient temperature.
2. Totally immerse components to be stripped into the lower, acidic layer. The required immersion time will vary. Average immersion time is 30 to 60 minutes.
3. After cleaning is complete, remove the parts from the bath and allow to drain over the tank.
4. Immediately dip rinse the parts in cold running water.
5. Rinse with high pressure water followed by a neutralizing alkaline dip.
6. A final dip rinse is recommended.

### Caution

- Rinse tanks should be arranged so that water **CANNOT** enter the Cee-Bee® J-91 bath!

## Solution Control

---

- Maintain an approximately 4" oil seal to prevent moisture from entering the lower acidic layer. The seal can be replenished by additions of Cee-Bee® J-91 Additive O.

## Safety, Handling, and Precautions

- **WARNING! DANGER! Contains concentrated sulfuric acid.** Corrosive.
- Do not allow any contact with eyes, skin or clothing. May cause burns or external ulcers.
- Do not take internally.
- Do not breathe any fumes, mist or vapor. Use with adequate ventilation.
- Wash thoroughly after handling.
- Wear approved acid resistant gloves, full face shield, or proper OSHA-approved respirator fitted with proper acid filter cartridge. Wear proper protective clothing sufficient to prevent any skin contact.
- In case of accidental contact with eyes. Flush with water for at least 15 minutes. Obtain prompt medical attention.
- For skin contact, flush with water for at least 15 minutes. If irritation persists, seek prompt medical attention.
- For inhalation, remove to fresh air.
- For ingestion, do NOT induce vomiting. Administer large quantities of water and immediately obtain medical attention.
- Wash clothing before reuse.
- **WARNING!** Bath may become corrosive to metals if contaminated with water.

## Contact Us

---

### United States

#### McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: [Aviation@McGean.com](mailto:Aviation@McGean.com)

### United Kingdom

#### McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: [Aviation@McGean-Rohco.co.uk](mailto:Aviation@McGean-Rohco.co.uk)

---

### Singapore

#### McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: [Info@ceebee.com.sg](mailto:Info@ceebee.com.sg)

### China

#### Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: [Info@ceebee.com.cn](mailto:Info@ceebee.com.cn)

**Cee-Bee<sup>®</sup> J-91** is a diphasic, highly active, cold paint, dry film lubricant, and resistant coatings remover.

**CAUTION:** BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 06/2021 (Rev. A2)