

Cee-Bee® Major Clean

Cee-Bee® Major Clean is a heavy-duty dry wash cleaner used for removing oxidation, carbon deposits greases and soils from painted and unpainted surfaces.

Conforms To

- Airbus
 - AIMS 09-00-002
 - CML 11-001
- AMS
 - AMS 1526B
 - AMS 1531D
- Boeing
 - BSS 7432
 - Maintenance Manual
 - 737
 - 747
 - 777
 - SOPM 20-60-01

Benefits

- Very effective for removal of tenacious soils in areas that are not adequately cleaned with other exterior cleaners.
- Restores luster to weathered paint by removal of oxides and traffic film.
- Non-crazing to acrylic plastic.
- Safe for use on all common aircraft structural metals, including aluminum, magnesium, titanium, mild steel, cadmium plated steel and high strength steel.
- May be used as a dry wash where water is not available for rinsing.
- Contains no phenolics, cyanides or heavy metal salts.

Properties

- Viscous, white liquid
- Contains chemically inert abrasives
- All surfactants are biodegradable
- Contains a high flash point petroleum hydrocarbon

Notes Prior to Handling

Before using your Cee-Bee® products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee® representative before proceeding.

Use Procedure

Cleaning with a Water Rinse

1. Use Cee-Bee[®] Major Clean as received or diluted with as much as 2 parts water.
 - a. For most soils 2 parts cleaner and 1 part water is optimum.
2. Apply a thin film of the cleaner using a white Scotch-Bright Pad, cellulose sponge, mop, soft bristle brush, non-atomizing spray equipment or rag.
3. Allow to dwell up to 5 minutes to penetrate soil.
4. Agitate surface.
 - a. For anodized aluminum or paint surfaces, a cellulose sponge is usually most efficient.
5. Thoroughly spray rinse with water.

Cleaning without a Water Rinse

1. Use Cee-Bee[®] Major Clean as received or diluted with as much as 2 parts water.
 - a. For most soils 2 parts cleaner and 1 part water is optimum.
2. Apply a thin film of the cleaner using a white Scotch-Bright Pad, cellulose sponge, mop, soft bristle brush, non-atomizing spray equipment or rag.
3. Allow to dwell up to 5 minutes to penetrate soil.
4. Agitate surface.
 - a. For anodized aluminum or paint surfaces, a cellulose sponge is usually most efficient.
5. Allow to dry for a few seconds, then wipe last haze from surface with clean, dry mops or rags.

Cold Weather Cleaning

1. Use ethylene glycol or deicing fluid in place of water to dilute Cee-Bee[®] Major Clean.
2. Do not use water rinse.
3. Wipe up excess cleaner and soils with clean dry mops or rags.
4. Allow to dry a few seconds, then wipe last haze from surface with clean, dry mops or rags.

Additional Information

- A heavy application of cleaner is less effective than a lighter film because excess cleaner cushions the surface against the effect of agitation.

Safety, Handling, and Precautions

- Can cause eye and skin irritation. Use rubber gloves and face shield or goggles.
- Use with adequate ventilation.
- Do not take internally.
- In case of accidental contact, flush with water. If irritation persists, seek medical attention.
- Keep away from sparks and open flame.
- Cleaner will not craze acrylic plastic windows. However, cleaner contains a mild abrasive and care should be taken not to agitate the cleaner on plastic surfaces to avoid scratching.
- Avoid contact with bearings.

Contact Us

United States

McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: Aviation@McGean.com

United Kingdom

McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: Aviation@McGean-Rohco.co.uk

Singapore

McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: Info@ceebee.com.sg

China

Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: Info@ceebee.com.cn

Cee-Bee[®] Major Clean is a heavy-duty dry wash cleaner used for removing oxidation, carbon deposits greases and soils from painted and unpainted surfaces.

CAUTION: BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 10/2021 (Rev. A3)