

Cee-Bee[®] WDO

Cee-Bee[®] WDO is a high-flash water-displacing oil designed to provide anti-rust protection.

Conforms To

- CFM
 - CP. 5078
- General Electric
 - C02-064
- International Aero Engines
 - OMat 10-091
- Pratt & Whitney
 - SPMC 126
- Rolls Royce
 - OMat 1036

Benefits

- Quickly displaces water from metal surfaces.
- Effectively prevents flash rusting of ferrous parts after cleaning, stripping or pickling.
- Provides outstanding protection during indoor storage.
- Tack-free, semi-dry film does not collect excessive dust and soil.
- Long solution tank life.
- Protective film easily removed.
- High flash point minimizes flammability hazard.
- Non-photochemically reactive.
- Low vapor toxicity.
- Safe for use on all common metals.
- Will not adversely affect paints, most plastics, glass or masonry.

Properties

- Dark red to brown, clear liquid
- Slightly viscous

Notes Prior to Handling

Before using your Cee-Bee[®] products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee[®] representative before proceeding.

Use Procedure

Dip Tank

1. Immerse parts in undiluted Cee-Bee[®] WDO at ambient temperature. The water displaced by the preferential wetting action of Cee-Bee[®] WDO will settle at the bottom of the tank.
2. After about 10 to 60 seconds, remove the parts and allow excess Cee-Bee[®] WDO to drain back into the tank.
3. Air dry.

Note:

- Tanks containing Cee-Bee[®] WDO should be equipped with a drain on or near the bottom of the tank to facilitate draining of immiscible water.
- Water, collected as an immiscible layer on the bottom of the tank, should be periodically drained off and fresh Cee-Bee[®] WDO added to raise the volume.

Spray-On

1. Spray on undiluted Cee-Bee[®] WDO at ambient temperature using non-atomizing spray equipment. Thoroughly wet the entire surface.
2. Allow parts to air dry.

Removal of Cee-Bee[®] WDO

- Cee-Bee[®] C-50 wipe solvent, Cee-Bee[®] Cleaner R-679 solvent/emulsion cleaner, or Cee-Bee[®] A-7X7 or Super Bee[™] 300LF/G hot tank cleaner can be used to remove the Cee-Bee[®] WDO protective film.



Safety, Handling, and Precautions

- Can cause eye and skin irritation - avoid contact. Use rubber gloves and face shield or goggles.
- Use with adequate ventilation.
- Do not take internally.
- In case of accidental contact with eyes or skin, flush thoroughly with water. If irritation persists, seek medical attention.

Contact Us

United States

McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: Aviation@McGean.com

United Kingdom

McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: Aviation@McGean-Rohco.co.uk

Singapore

McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: Info@ceebee.com.sg

China

Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: Info@ceebee.com.cn

Cee-Bee[®] WDO is a high-flash water-displacing oil designed to provide anti-rust protection.

CAUTION: BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 06/2021 (Rev. A2)