

Eldorado PR-3500

Eldorado PR-3500 is a high-performance, solvent -based, viscous stripper, used to strip aircraft primers, epoxy, polyurethane, and other organic coatings from metal surfaces.



Conforms To

- AMS
 - AMS 1375
- ARP
 - ARP-1755
- Boeing
 - D6-17487
- Douglas
 - CSD-1
- Embraer
- Military
 - MIL-R-81294
 - Type I, Class 1
 - Type II, Class 1
 - Type IV, Class 1
- Rolls Royce



Benefits

- Safe on aluminum, cadmium, magnesium, ferrous alloys, titanium, and high strength steel.
- Low vapor toxicity.

McGeen® recommends checking the most recent specifications for updated information.



Properties

- Neutral pH
- Contains phenol and sodium chromate



Notes Prior to Handling

Before using your Cee-Bee® products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee® representative before proceeding.

Use Procedure

Works well at temperatures ranging from 45° to 95°F (7° to 35°C). Spray or brush undiluted Eldorado PR-3500 paint strip-per onto surface. Allow at least 15 minutes for the paint to be loosened. Agitate to dislodge loosened paint, then squeegee stripper residues and paint from the surface. Plastics sheeting placed under the aircraft have been found to be useful to facili-tate the collection of paint stripper residue.

Conditions of humidity and temperature will dictate dwell time. Clean stripped surface with an approved cleaner to remove all stripper residues.

Safety, Handling, and Precautions

Before using your Cee-Bee® products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee® representative before proceeding.

If Eldorado PR-3500 accidentally contacts the skin, flood the affected area with water. If further treatment is required apply some ointment or salve to replace oils and soothe the skin. In case of contact with eyes, flush thoroughly with water and seek medical attention.

Eldorado PR-3500 must be used with adequate ventilation, due to the high-chlorinated solvent content. When application is made on a large scale, full wash rack gear consisting of rubber boots, gloves, foul-weath-er gear, and facemask should be worn to minimize contact of the material with the skin.

Contact Us

United States

McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: Aviation@McGean.com

United Kingdom

McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: Aviation@McGean-Rohco.co.uk

Singapore

McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: Info@ceebee.com.sg

China

Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: Info@ceebee.com.cn

Eldorado PR-3500 is a high-performance, solvent -based, viscous stripper, used to strip aircraft primers, epoxy, polyurethane, and other organic coatings from metal surfaces.

CAUTION: Before using any of these products, you must become completely familiar with the safety and hazard information contained in our safety data sheets regarding these products. McGean-Rohco, Inc. (the seller) presents the information contained herein without warranty and disclaims any liability from its use or misuse. Seller recommends use of the information Seller's products solely in commercial processes which are specified by Seller and which do not violate any third party patent rights or any laws or regulations. The seller makes no warranties, express or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose except as expressly stated in the seller's sales contract or sales acknowledgement form.



Revision: A2 (5/2025)